# HINGED HATCH

Extra Heavy Duty
Access Covers



# Airport references



Lisbon International Airport
Portugal
AGL network



Paris Orly Airport
France
AGL network




Dublin International Airport
Ireland
AGL network



Milan Linate International Airport
Italy
Anchoring application



Geneva International Airport
Switzerland
Electrical network




Abu Dhabi International Airport
United Arab Emirates
AGL network

# HINGED HATCH F900 Extra heavy duty

## The benefits

**Safety**
Safety bar preventing unexpected closure
Hole for grounding connection

**One man operation**
Lifting effort <25 kg thanks to the stainless steel mechanical spring strut



**Adaptability**
Removable and interchangeable locking systems

**Large clear opening up to 914 x 1883 mm**
Removable beam for unobstructed access to the chamber

**FOD (Foreign object damage) compliancy**
In-house designed to ensure zero spare parts debris


**Maintenance free**

Scan this QR code to see the HH video on YouTube

Hinged Hatch Video on YouTube

# HINGED HATCH F900 Extra heavy duty

## Hinged and assisted access cover with frame



**FOD (Foreign object damage) compliancy**
In-house designed to ensure zero spare parts debris

**Maintenance free**


**Adaptability**
Removable and interchangeable locking systems


**One man operation**
Lifting effort <25 kg thanks to the stainless steel mechanical spring strut

**Safety**
Safety bar preventing unexpected closure
Hole for grounding connection

**Large clear opening up to 914 x 914 mm**

- Ductile iron access cover and frame
- SG iron 500-7 - ISO 1083 / EN1563
- F900 to EN124-2 - Third Party certified
- 4L patented design anti-slip surface
- Polychloroprene cushioning insert glued to the cover
- 10 years warranty mechanical stainless steel strut with reflective tape
- Safety bar blocking at 90°
- Stainless steel locking system
- Frame equipped with 4 lifting rings
- Frame and cover equipped with a drilled and tapped hole for grounding connection








| Product reference | Clear opening O x O' (mm) | Overall dimensions A x A' (mm) | Height H (mm) | Weight (kg) |
|---|---|---|---|---|
| HH9S091091 | 914 x 914 | 1146 x1146 | 127 | 255 |
| HH9S076076 | 760 x 760 | 994 x 1003 | 127 | 196 |

Class D400 available : please enquire

# HINGED HATCH F900 Extra heavy duty

## Hinged and assisted access cover with frame



**FOD (Foreign object damage) compliancy**
In-house designed to ensure zero spare parts debris

**Maintenance free**


**Adaptability**
Removable and interchangeable locking systems

**One man operation**
Lifting effort <25 kg thanks to the stainless steel mechanical spring strut

**Safety**
Safety bar preventing unexpected closure
Hole for grounding connection

**Large clear opening up to 914 x 1883 mm**
Removable beam for unobstructed access to the chamber

- Ductile iron access cover and frame
- SG iron 500-7 - ISO 1083 / EN1563
- F900 to EN124-2 - Third Party certified
- 4L patented design anti-slip surface
- Polychloroprene cushioning insert glued to the cover
- 10 years warranty mechanical stainless steel strut with reflective tape
- Safety bar blocking at 90°
- Stainless steel locking system
- Frame equipped with 8 lifting rings
- Frame and cover equipped with a drilled and tapped hole for grounding connection
- Central beam removable by unscrewing stainless steel screws




| Product reference | Clear opening O x O' (mm) | Overall dimensions A x A' (mm) | Height H (mm) | Weight (kg) |
|---|---|---|---|---|
| HH9S189091 | 914 x 1883 | 1146 x 2114 | 127 | 521 |
| HH9S157076 | 760 x 1570 | 994 x 1830 | 127 | 403 |

Class D400 available : please enquire

# HINGED HATCH F900 Extra heavy duty

## Choose your locking system




### Stainless steel tight locking system

- Enhance stability
- Allow watertightness (please enquire)
- Specific key opening for a secured access
- FOD compliant



### 4 Stainless steel bolts locking system

- Enhance stability
- Suitable for traffic area



### Stainless steel ‘push and lock’ locking system without key


- Quick opening and closure
- No specific key required
- FOD Compliant



### Stainless steel ‘push and lock’ locking system with key

- Quick opening and closure
- Specific key required for a secured access
- FOD Compliant

# HINGED HATCH F900 Extra heavy duty
## Choose your options




### Watertightness

- Please enquire



### Cable way out

- Removable plug on covers (Ø 80 mm)
- Permanent hole on covers (100 x 45 mm)



### Safety grids

- Various customised safety grids are available for operators' safety



### Specific coating

- Please enquire




### Customised badging

- Network or chamber identification, name and logo badging

ejco.com



Americas
**+1 800 874 4100**

EMEA
Europe,Middle East,
Africa and South East Asia
**+33 344 08 28 00**

Asia-Pacific
**+61 73216 5000**

**EMEA**
ZI de Marivaux
60149 Saint Crépin Ibouvillers
France
+ 33 (0) 3 44 08 28 47
emea.airportport@ejco.com

Registered
Trademarks

CAVANAGH®
NORINCO®
TELECOM®
SELFLEVEL®
ERMATIC®
CHILDSAFETY®
DEFENSO®
NORGUSS®
CABLECOM®
NORLONG®
MAXIMO®
AQUERA®

**Hinged Hatch**
**Extra Heavy Duty**
**Access Covers**
**EJ© - 4/2018**