

RETROMAX Optimised Capacity Drainage Gratings ULTRA™ Specification



KD57D



KD44D

Features:

- Manufactured to BS EN 124 class D 400
- BSI Kitemarked for third party assurance of quality
- ULTRA™ products comply with HA 104
- Suitable for carriageway and fast moving traffic applications
- AMP™ patented anti-movement technology frames
- Non-rock wedge seats for stability and silent operation
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish

Benefits:

- Large over base size to spread applied loads from crumbling gully faces to a firm bedding area
- Superior drainage capacity
- Prolongs gully life-span

Options:

- Right hand hinging available
- Locking with standard bolts

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	HA102	Waterway (cm ²)	Weight (kg)	Gully
KD52D6	500 x 350	645 x 450	150	R	1152	45	450
KD54D	600 x 450	750 x 550	100	Q	1815	48	450
KD57D**	750 x 450	910 x 542	150	Q	2262	78	450
KD44D6*	1000 x 450	1170 x 547	100	P	3805	100	450

*Twin double triangular, three point suspension non-rock product and is not hinged and cannot be locked.

**Dished