

D 400
Drainage Gratings
INTEGRITY™ Specification



KD500



KD500P



KD410

Features:

- Manufactured to BS EN 124 class D 400
- BSI Kitemarked for third party assurance of quality
- Suitable for lower intensity traffic
- AMP™ patented anti-movement technology frames
- Captive hinged for easy access and increased security
- Non-rock three point suspension for silent operation (Double Tri)
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish

Options:

- Right hand hinging available on captive hinged gratings
- Locking with standard bolts

Captive Hinged

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	HA102	Waterway (cm ²)	Weight (kg)	Gully	Type
KD50DP	420 x 420	570 x 505	100	-	915	43	450	Pedestrian, Hinged
KD500	375 x 430	530 x 525	100	-	1086	31	450	Hinged
KD502*	420 x 420	570 x 510	100	-	1216		450	Dished, Hinged
KD500P	380 x 440	530 x 525	100	-	812	31	450	Hinged
KD51D	380 x 310	480 x 370	100	-	876	26	375	Hinged
KD51DP	380 x 310	560 x 410	100	-	370	33	375	Pedestrian, Hinged
KD52D	495 x 345	645 x 440	100	-	1140	43	450	Hinged

*Right hand hinging not available

Double Triangular

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	HA102	Waterway (cm ²)	Weight (kg)	Gully	Type
KD410	400 x 440	550 x 525	100	R	1138	34	450	Double Tri