

PROPRIETARY Drainage Gratings



D58-4



D58-2



D46-1

Features:

- Manufactured to BS EN 124 class C 250 as specified
- BSI Kitemarked for third party assurance of quality
- Suitable for areas with slow moving traffic
- Captive hinged design (except D46-1)
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish

Blogully

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	Weight (kg)	Dish Depth (mm)	Flanges
D58-2	340 x 170	400 x 200	145	25	15	3
D58-3	340 x 170	400 x 200	145	27	15	4
D58-1	170 x 170	200 x 200	125	18	15	3

Congully

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	Weight (kg)	Dish Depth (mm)	Flanges
D58-4	360 x 240	375 x 250	145	26	30	3
D58-5	360 x 240	375 x 250	145	26	30	4

Gully Chute Connector

Standard Sizes

Code	Over Grate (mm)	O/all Frame (mm)	Frame Depth (mm)	Weight (kg)	Dish Depth (mm)	Flanges
D46-1	415 x 320	515 x 250	180	23	-	-

